



























Laser head

Brand [Brand Name]

Motor direction Positive

Homing mode Incremental Mode

Model BSD3/06/12/20/40/60K-CAT

Focus control port/servo Node 5:调焦Axis

Manual Speed

Speed: 0.30m/min

Manual feed: 0.60m/min

Auto Speed

Speed: 6.00m/min

Acceleration: 1500.00m/s²

Acc time: 100ms

Protective mirror alarm temperature setting

Protect Temp Alarm

Temp Alarm: 50.00 °C

Temp rise rate: 14.00 °C

OpticalRatioAndVer

ViewFirmwareVerAndCheckPar

Gas Pressure Parameter Setting

Gas Pressure Alarm

Deviation allowable: 70.00 %

Scattered light alarm设置

Scattered light alarm

Cavity Alarm Temperature Setting

Cav Temp Alarm

Temp Alarm: 40.00 °C

Temp rise rate: 50.00 °C

DewPointAlarmSet

Dewpoint Temp Alarm

Focus adjmt

8.0000mm

0.60m/min

10.00mm

Restore default data

OpticalRa... (1)100:200

Deviation allowa... 20.00 %

Temp Alarm: 1950.00

Temp rise rate: 2000.00

Temp Alarm: 2000.00

Temp rise rate: 2000.00

Temp Alarm: 2000.00

Temp rise rate: 2000.00



